

## Intex PlasterX® Paper Joint Tape

### 1. Identification

#### Product Details:

<b>Product Code:</b>	5PT20S, 5PT75S, 5PT150S
<b>QTY per Carton:</b>	10rolls/20rolls/60rolls
<b>Application:</b>	Paper reinforcing tape for strengthening and finishing joints of interior drywall panels. A center creasing process allows easy folding for use at corners.
<b>Instructions for use:</b>	Make sure that the surface to work on is clean (no dust nor grease). First apply a liberal coat of joint compound, about 2 to 3 wide along the entire joint. Throw away any compound that has dried pieces. While the compound is still wet, embed our paper joint tape by centering the tape directly over the joint. Use a taping knife to press the tape into the joint compound. Remove excess compound over and around the tape to level the surface. Apply a second coat of joint compound that extends beyond the first coat 7 to 8 . Let it dry completely. Apply a thin finishing coat to each joint. Once all dried sand lightly with a fine abrasive.
<b>Temperature of use:</b>	Not recommended for areas exposed to sustained temperatures over 50°C
<b>Technical Features:</b>	Tests:
<b>Composition:</b>	Paper Strength: 3.85 N/mm Material Body - Kraft paper, (EN 13963)
<b>Dimensions:</b>	
<b>Roll Length:</b>	75m - Paper Dimensional Stability:(EN 13963) Length - 0.1% Width - 0.1%
<b>Paper Width:</b>	50mm
<b>Warehouse Recommendations:</b>	Protect from water, moisture and incompatible materials, such as strong acids, strong bases, strong oxidising agents, sodium and other metallic anhydrides.
<b>Manufacturer/ Supplier By:</b>	<b>Intex Group International</b> Pty Ltd (ACN 163012039) 91 - 115 Link Drive, Campbellfield, Victoria 3061, Australia <b>+61 3 9357 9299</b> (or 1300 107 108 within Australia) <b>Intex New Zealand</b> Pty Ltd (NZCN 7388136) 13 Mahunga Drive, Mangere Bridge, Auckland 2022, New Zealand <b>+64 6 377 7255</b> (or 0800 278 276 within New Zealand)  <b>13 11 26</b> (AU Poisons Info Centre) <b>0800 764 766</b> (NZ Poisons Info Centre)