

Intex

Lumo



WARNING: Read and become familiar with this manual BEFORE operating unit.

Intex Lumo®

Corded LED Worklight

6000 Lumens

Product Description:

Designed for cool non-glare illumination and built TradeTuff® for the most demanding work-site conditions. Features advanced Surface-Mount Technology, delivering true representation of colours, optimised colour temperature and even beam patterns, improving lighting effect and efficiency.

Intex Lumo® Operation:

1. To turn on the Worklight press the Power dial **(Figure B)**.
2. Adjust the brightness by rotating the stepless Power dial clockwise to increase and anticlockwise to dim (10%-25%-50%-75%-100%).
3. To turn off the Worklight press the Power dial.



Figure B

SLP6000 Specifications:

| | |
|-----------------------------------|-------------------------------------|
| Lumens with Floodlight Attachment | 480-4800 |
| Socket Output | 8A 1600W |
| Lumens (lm) | 600-6000 |
| Watts (W) | 60 |
| Voltage (V) | AC200-250V/50-60HZ |
| Colour Temperature (K) | 5500-6500 |
| Colour Rendering Index (Ra) | CRI>70 |
| Power Cable | 3m 3*1.5sqmm H07RN Cable + 10A Plug |
| Water Resistance Rating | IP54 |
| Impact Resistance Rating | IK07 |
| Storage Temperature | -20° to 50° |
| Working Temperature | -10° to 40° |
| Weight (kg) | 3.06 |
| Dimensions (mm) | 304 x 238 x 102 |
| Warranty | 12 Months |

AS/NZS 60598.2.5:2015, AS/NZS 61347.1:2016+A1:2018, AS 61347.2.13:2018

Contents:

Corded LED Worklight
Instruction Manual

Warnings:

- Wear safety goggles whilst operating (user and bystanders).
- Avoid looking directly into the beam.
- Do not use the Worklight near open flames.
- Do not cover the lens whilst operating to prevent overheating.
- Do not contaminate the lens with organic solvents.
- Take care to position the Worklight in a careful manner, ensuring the light is properly supported by the stand.
- When using at a height of 3m or greater, take extra precaution to prevent falling objects causing harm to bystanders and or nearby equipment.



intexinternational.com

Lumo® is a registered Trademark of Intex International
The information contained in this brochure was correct at the time of printing. E&OE